Switch?

A COMPANY TO THE

- Many ports
- L2/Ethernet traffic
- VLAN



• Wire-speed on MikroTik switches

Router?

- L3/IP Traffic
- Firewall
- Tunnels



• BGP/OSPF etc.

MikroTik switch advantages

- + Price!
- + Number of ports
- + wire speed
- RouterOS advanced features decreases speed

MikroTik Switches



MikroTik switches

- SwOS
- SwOS/RouterOS
- RouterOS

Before MikroTik RouterOS 6.41

- Configuration was difficult
- Non scalable
- We put big effort to make it easier

MikroTik RouterOS 6.41

- Main configuration is done at /interface bridge
- /interface bridge ports controls switch configuration
- VLAN configuration is done at bridge settings

hw=yes or hw=no

- hw=yes, wire speed is available, switch chip is used;
- hw=no, CPU is used to process packets, no wirespeed

hw=yes and wire speed

RouterBoard/[Switch Chip] Model	Features in Switch menu	Bridge STP/RSTP	Bridge MSTP	Bridge IGMP Snooping	Bridge VLAN Filtering	Bonding
CRS3xx series	+	+	+	+	+	+
CRS1xx/CRS2xx series	+	+	-	+	-	-
[QCA8337]	+	+	-	-	-	-
[AR8327]	+	+	-	-	-	-
[AR8227]	+	+	-	-	-	-
[AR8316]	+	+	-	-	-	-
[AR7240]	+	+	-	-	-	-
RB750Gr3 [MT7621]	+	-	-	-	-	-
RB1100AHx4 [RTL8367]	+	-	-	-	-	-
[ICPlus175D]	+	-	-	-	-	-

hw=no on every other device with bridge

hw=yes or hw=no

- hw=yes, wire speed is available, switch chip is used;
- hw=no, CPU is used to process packets, no wire speed

Wire speed

- RSTP and MSTP
- VLAN
- IGMP Snooping
- Bonding
- CRS326, CRS328, CRS317

Wire speed

• RSTP

- IGMP Snooping
- Bonding
- CRSIxx and CRS 2xx series

Configuration examples

Simple switch



Simple switch [or bridge]

- /interface bridge add
- /interface bridge port add bridge=bridge l interface=ether3
- /interface bridge port add bridge=bridge l interface=ether5

Trunk and access ports CRS3xx



Trunk and access ports CRS3xx

- /interface bridge add
- /interface bridge port add bridge=bridge l interface=ether7
- /interface bridge port add bridge=bridge l interface=ether 19
- /interface bridge port add bridge=bridge l interface=ether21

Trunk and access ports CRS3xx

- Configure VLAN
- /interface bridge port set ether7 pvid=1000
- /interface bridge vlan add bridge=bridge1 tagged=bridge1,ether1 untagged=ether7 vlan-ids=1000
- /interface bridge port set ether19,ether21 pvid=1001
- /interface bridge vlan add bridge=bridge1 tagged=bridge1,ether1 untagged=ether7 vlan-ids=1001
- Enable VLAN filtering /interface bridge add name=bridge1 vlan-filtering=yes

CRSIxx/CRS2xx



CRSIxx/CRS2xx

- /interface bridge add
- /interface bridge port add bridge=bridge l interface=ether3
- /interface bridge port add bridge=bridge l interface=ether5
- /interface bridge port add bridge=bridge l interface=ether7

CRSIxx/CRS2xx

- /interface ethernet switch vlan
- add ports=ether1,ether3 switch=switch1 vlanid=1000
- add ports=ether1,ether5,ether7 switch=switch1
 vlan-id=1001

Large scalable network example



Large network example

- Each CRS317+CRS326 up to 336 I Ggbps wired clients
- CRS317+CRS317 up to 224 10Gbps wired clients



Large network example

- DHCP-server configured on GW#XVLAN interface
- VLAN1000,1001,1002,1003,100x are distributed to end clients

- /interface bridge add fast-forward=no
 name=bridge1 priority=0x100 vlan-filtering=yes
- /interface bridge port add bridge=bridge1 frametypes=admit-only-vlan-tagged interface=sfpsfpplusx

- /interface bridge vlan
- add bridge=bridge1 tagged="bridge1,sfp-sfpplus1,sfp-sfpplus2,sfp-sfpplusx" vlanids="1000,1001,1002,100X"



- /interface bridge add fast-forward=no name=bridge1 priority=0x1000 vlan-filtering=yes
- /interface bridge port add bridge=bridge1 frametypes=admit-only-vlan-tagged interface=sfpsfpplus1, sfpplusx

- /interface bridge vlan
- add bridge=bridge1 tagged="bridge1,sfp-sfpplus1,sfp-sfpplus2,sfp-sfpplusx vlan-ids="1000,1001,1002,200x"



- /interface bridge add fast-forward=no name=bridge | vlan-filtering=yes
- /interface bridge port
- add bridge=bridge1 interface=ether2 pvid=1000
- add bridge=bridge1 interface=ether3 pvid=1001
- add bridge=bridge1 interface=ether4 pvid=1002
- add bridge=bridge1 interface=ether5 pvid=100x
- add bridge=bridge1 interface=sfp-sfpplus1
- add bridge=bridge1 interface=sfp-sfpplus2

- /interface bridge port
- add bridge=bridge1 interface=ether2 pvid=1000
- add bridge=bridge1 interface=ether3 pvid=1001
- add bridge=bridge1 interface=ether4 pvid=1002
- add bridge=bridge1 interface=ether5 pvid=100x
- add bridge=bridge1 interface=sfp-sfpplus1,sfp-sfpplus2
- /interface bridge vlan
- add bridge=bridge1 tagged=bridge1,sfp-sfpplus1 untagged=ether2 vlan-ids=1000
- add bridge=bridge1 tagged=bridge1,sfp-sfpplus1 untagged=ether3 vlan-ids=1001
- add bridge=bridge1 tagged=bridge1,sfp-sfpplus1 untagged=ether4 vlan-ids=1002
- add bridge=bridge1 tagged=bridge1,sfp-sfpplus1 untagged=ether5 vlan-ids=100x

Switch configuration misc

- Bridge priority configuration
- Highest on GW, then on C#1 and C#2

